


PRODUCT BRIEF



Intel® Wireless-AC 9260

5th Generation Intel 802.11ac, Dual Band, 2x2 Wi-Fi + Bluetooth⁺ 5

Intel® Wireless-AC 9260

Ultra Wi-Fi. Ultra Features. Ultra Connected Experience



The Intel® Wireless-AC 9260 adapter supports Bluetooth⁺ 5 and 2x2 802.11ac Wi-Fi including wave 2 features such as 160MHz channels, delivering up to 1.73Gbps¹ and downlink MU-MIMO. These new features deliver a significant increase in user speeds in dense deployments, supporting fast downloads and long battery life compared to legacy 802.11ac devices. Combined with Intel® Core™ processors and exceptional Intel wireless innovations, the Intel® Wireless-AC 9260 can provide Gigabit download speed¹ and dramatically improve your connected experience at home, work, or on the go.

5TH GENERATION INTEL 802.11AC WIRELESS

**Faster Speed
Better Coverage
Larger Capacity**

**802.11ac, 2x2, Dual Band,
160MHz, MU-MIMO**

Intel® Wireless-AC 9260 enables smoother streaming of higher resolution videos, fewer dropped connections, less congestion, and faster speeds farther away from the router, enabling DL MU-MIMO and 160MHz channel use.

When using 160MHz channels, Intel® Wireless-AC 9260 can deliver over 5x faster Wi-Fi speeds (up to 1.73Gbps) than 802.11n and double the speed of legacy 802.11ac².

Downlink MU-MIMO allows an Access Point to simultaneously transmit data to multiple clients and potentially improve overall downlink network capacity by over 3x³.

Bluetooth⁺ 5

Bluetooth⁺ 5 provides 4x⁴ range over BT4.2 with the same power, enabling coverage throughout the home. BT5 also doubles the transmit speed for faster transmissions thereby reducing the overall power.⁴ Additionally, BT5 adds new enhanced data broadcasting enabling seamless services such as location-based services and simpler pairing for BT devices.

Microsoft Windows 10* Ready

Full support for latest Microsoft Windows 10* OS.

M.2 2230 Form Factor

M.2 2230 modules enable system configuration and platform usages flexibility with the use of a standard Key A or E socket for attaching the module.

EXPERIENCE THE INTEL® DIFFERENCE

**Worldwide Regulatory Support
Intel® Dynamic Regulatory Solution**

Enables worldwide regulatory compliance on a single adapter SKU. The Intel® Wireless-AC 9260 detects its location and automatically optimizes the Wi-Fi settings to local regulatory requirements, maximizing performance in each geography, simplifying travel experience and global enterprise procurement. Future regulatory changes are easily managed during the product life cycle.

**Wireless Functionality in
Pre-boot Environment**

Support for Wi-Fi network and BLE HID connectivity in the platform's UEFI (Unified Extensible Firmware Interface) environment during its boot stage. This capability enables use cases like OS recovery over Wi-Fi and BLE-based keyboard and mouse connectivity in this pre-boot environment.

Wirelessly Project to the Big Screen

Watch your 2-in-1 or laptop content instantly without wires on the big HD screen with stunning image clarity and sound using Wi-Fi Miracast*. Stream movies, videos, games, photos, connect with friends, and more—experience it all, bigger and better than ever before.

BUSINESS-CLASS WIRELESS

Intel® vPro™ Technology⁵

Supports Intel's hardware-based security and management features built into Intel® Core™ vPro™ processors and chipsets that enables IT to manage PCs virtually anywhere, anytime while reducing deployment costs, improving security and ROI.

Intel® Active Management Technology⁶

Using integrated platform capabilities and popular third-party management and security applications, Intel® AMT allows IT or managed service providers to better discover, repair, and help protect their networked computing assets. Intel® AMT is a feature of Intel® Core™ processors with Intel® vPro™ technology.

INTEL® WIRELESS-AC 9260 TECHNICAL SPECIFICATIONS

GENERAL

| | |
|--|--|
| Dimensions (H x W x D) | M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] |
| Weight | M.2 2230: 2.9g |
| Antenna Diversity | Supported |
| Radio ON/OFF Control | Supported |
| Connector Interface | M.2: PCIe, USB |
| Operating Temperature (Adapter Shield) | 0°C to +80°C |
| Humidity Non-Operating | 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) |
| Operating Systems | Microsoft Windows 10*, Linux* (limited feature support), Chrome* |
| Wi-Fi Alliance | Wi-Fi CERTIFIED* a/b/g/n/ac with wave 2 features, WMM*, WMM-PS*, WPA*, WPA2*, WPS2*, Protected Management Frames, Wi-Fi Miracast* as Source, and Wi-Fi Direct |
| IEEE WLAN Standard | IEEE 802.11a/b/g/n/ac, 802.11d, 802.11e, 802.11h, 802.11i, 802.11w; 802.11r, 802.11k, 802.11v pending OS support; Fine Timing Measurement based on 802.11REVmc |
| Roaming ⁷ | Supports seamless roaming between access points |
| Bluetooth ⁸ | Bluetooth ⁸ 5 |

SECURITY⁹

| | |
|---|---|
| Authentication | WPA* and WPA2*, 802.1X (EAP-TLS, TTLS, PEAP,EAP-SIM, EAP-AKA, EAP-AKA') |
| Authentication Protocols | PAP, CHAP, TLS, MS-CHAP*, MS-CHAPv2 |
| Encryption | 64-bit and 128-bit WEP, TKIP, 128-bit AES-CCMP |
| Wi-Fi Direct* Encryption and Authentication | WPA2-PSK, AES-CCMP |

COMPLIANCE

| | |
|----------------|---|
| Regulatory | For a list of country approvals, please contact your local Intel representatives. |
| US Government | FIPS ⁹ , FISMA |
| Product Safety | UL, C-UL, CB (IEC 60950-1) |

PRODUCT NAME

MODEL NUMBER

VERSION

| | | |
|-------------------------|---------|---|
| Intel® Wireless-AC 9260 | 9260NGW | 802.11ac wave 2, 2x2, Bluetooth* 5, PCIe, USB, M.2 2230 |
|-------------------------|---------|---|



For more information on Intel® Wireless products, visit intel.com/wireless

¹ Based on the theoretical maximum bandwidth enabled by 2x2 802.11ac 160MHz implementations. Actual wireless throughput and/or range will vary depending on your specific operating system, hardware and software configurations. Check with your device manufacturer for details.

² 802.11ac 160MHz provides 1.73Gbps maximum throughput, 2x more than 802.11ac 80MHz (867Mbps) and 5x more than 802.11n 40MHz (300Mbps) based on industry standards.

³ 802.11ac downlink MU-MIMO technology allows concurrently serving multiple devices simultaneously, in turn increasing network capacity potentially by over 3x while improving per-user throughput based on industry standards.

⁴ Bluetooth⁸ 5 Specifications, <https://www.bluetooth.com/~media/files/specification/bluetooth-5-faq.ashx?la=en>

⁵ Intel® vPro™ Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment. To learn more visit: <http://www.intel.com/technology/vpro>

⁶ Requires activation and a system with a corporate network connection, an Intel® AMT-enabled chipset, network hardware and software. For notebooks, Intel® AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating or powered off. Results dependent upon hardware, setup & configuration. For more information, visit <http://www.intel.com/technology/platform-technology/intel-amt>

⁷ Roaming is supported only within each respective band and mode of access points.

⁸ Some security solutions may not be supported by your device operating system and/or by your device manufacturer. Check with your device manufacturer for details on availability.

⁹ Microsoft Windows 7*, Microsoft Windows 8.1* and Microsoft Windows 10*.

*The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by [licensee name] is under license.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit <http://www.intel.com/benchmarks>.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including without limitation, liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, lifesaving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit <http://www.intel.com/wireless>.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

This device has not been authorized as required by the rules of the Federal Communications Commission.

This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained.

Intel, the Intel logo, and Intel are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and/ or other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2017 Intel Corporation. All rights reserved.