


| REVISION | | |
|----------|-------------|----------|
| REV. | DESCRIPTION | DATE |
| 1.0 | NEW ISSUE | 12/29-15 |




CONN#1



CONN#2



M0501649(内插)
M0501649(外插)



CONN#2

ELECTRICAL CHARACTER:

- 100% OPEN&SHORT TESTING
- WITHSTANDING VOLTAGE:DC 300V 0.1Sec
- INSULATION RESISTANCE:20M Ohms(Min)
- CONDUCTIVE RESISTANCE:1.0 Ohms(Max)

CONN#1

CONN#2

| | | |
|---|-------|----|
| 1 | _____ | 1 |
| 2 | _____ | 2 |
| 3 | _____ | 3 |
| 4 | _____ | 5 |
| 5 | _____ | 6 |
| 6 | _____ | 7 |
| 7 | _____ | 8 |
| 8 | _____ | 9 |
| 9 | _____ | 10 |

SHELL

SHELL

| 7 | OVERMOLD | 3.5g | YL0103011 | PVC 25P BLUE UL94V-0 |
|-----|-------------|------|-----------|------------------------------|
| 6 | OVERMOLD | 3.5g | YL0103014 | PVC 45P BLUE UL94V-0 |
| 5 | INNERMOLD | 1.7g | YL0103013 | PE LOW DENSITY |
| 4 | CONN#2 | 1 | YL0102234 | USB3.0 MicroB 超薄 铜壳镀镍 端子镀金1u |
| 3 | CONN#1 | 1 | YL0102231 | USB 3.0 AF 短体 镀金1u |
| 2 | CABLE | 1 | QT0601005 | 电子线 7/0.12TC L=0.03M |
| 1 | CABLE | 9 | QT0601011 | 电子线 7/0.12TC L=0.023M |
| NO. | DESCRIPTION | QTY. | PART NO. | MATERIAL |
| | | | J | |
| | | | | |
| | | | | |
| | | | | |